





D5272-3 AFT TUBE

- NOTES:**
- 1) MATERIAL: 6061-T6/T62/T6510/T6511 SEAMLESS TUBING
PER WW-T-700/8
OR QQ-A-200/8 OR QQ-A-225/8
OR AMS 4080 OR AMS 4082 OR AMS 4083
OR ASTM B210 OR ASTM B241
REF DART SPEC M6061T6T1.500W0.120
 - 2) FINISH: ANODIZE BLACK PER MIL-A-8625F TYPE I OR IB OR IC OR II OR IIB CLASS 2 AFTER BENDING
 - 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
 - 4) UNITS: INCHES UNLESS OTHERWISE NOTED
 - 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
 - 6) IDENTIFICATION: IDENTIFY WITH DART P/N "D5272-3" PER DART QSI 044, SECTION 6.1
 - 7) WEIGHT: 0.46 lbs
 - 8) NO CRUSHING IN HATCHED AREA

RELEASED
2015-12-07

APPROVED

DESIGN	CC	DART AEROSPACE USA, INC EUGENE, OREGON, USA	
DRAWN	CC		
CHECKED	VS	DRAWING NO.	REV. A
MFG. APPR.	JLM	D5272	SHEET 2 OF 2
APPROVED	HS	TITLE	SCALE
DE APPR.	DS	TUBE	NTS
DATE	15.06.10	COPYRIGHT © 2015 BY DART AEROSPACE USA, INC THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE USA, INC	